Stainless Steel Solid Door Reach-In Refrigerator

Features

- -CFC free refrigerant and foam insulation.
- -Equipped with an electronic thermostat and digital LED temperature display for precise control and convenient reading.
- -Features a self-closing swing door for added convenience.
- -The magnetic gasket can be replaced without the need for any tools.
- -External construction 430 stainless steel framework.
- -Internally constructed with 304 stainless steel.
- -Incorporates auto defrosting and auto evaporation mechanisms to prevent condensation. Condensation
- -The coated copper tube, boasting a sturdy 0.7mm thickness, ensures durability.
- -Crafted from a single bent tube, minimizing the risk of leaks with only two welding joints.
- -The condenser is efficiently positioned inside the condensation pan to facilitate the evaporation of excess water.
- -Adjustable and heavy-duty epoxy-coated wire shelves for flexible storage options.
- -Comes with easy-to-mount 4" casters (front casters equipped with brakes), standard with all units.
- -Electrical specifications: 115/60/1 with a NEMA 5-15P plug and a 10ft cord.

Temperature

- -Interior temperature range: 1°C to 6°C (33°F to 46°F)
- -Ambient temperature upto 45°C (113°F)







C-35BR/C-48BR/C-54BR



www.sub-equip.com

Only two

C-81BR

Specifications

Model	Doors	Ext. Dimensions W x D x H (in)	Storage Capacity(cu./ft)	Shelves	V/Hz/Ph	AMPS	Power	NEMA PLUG	Ship Weight(lbs)	Ship Data W x D x H (in)
C-19BR	1	26 3/4 x 25 5/8 x 80 7/	′8 16.4	5	115/60/1	3.5	350W/0.47HP	5-15P	177	29 1/4 x 28 x 88 3/4
C-27BR	1	26 3/4 x 32 3/4 x 80 7/	′8 21.5	5	115/60/1	3.5	350W/0.47HP	5-15P	331	29 1/4 x 35 x 88 3/4
C-35BR	2	39 1/2 x 32 3/4 x 80 7/8	8 32.7	10	115/60/1	4	500W/0.67HP	5-15P	441	41 7/8 x 35 x 88 3/4
C-48BR	2	48 x 32 3/4 x 80 7/8	40.1	10	115/60/1	5.5	600W/0.81HP	5-15P	460	50 1/2 x 35 x 88 3/4
C-54BR	2	54 x 32 3/4 x 80 7/8	45.2	10	115/60/1	7	700W/0.94HP	5-15P	485	56 3/8 x 35 x 88 3/4
C-81BR	3	80 3/4 x 32 3/4 x 80 7/	′8 68.5	15	115/60/1	7.5	800W/1.08HP	5-15P	706	83 x 35 x 88 3/4









