

❖ Refrigerated Counter Range



◆ Features

- CFC free refrigerant and foam
- Complete structure interior&. exterior in stainless steel AISI 304 with round internal edges for easy cleaning
- Insulation 60 mm thickness
- Ventilated refrigeration compartment gives a better air circulation
- Auto defrosting and auto evaporation of condensation water
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Self-closing door
- Magnetic gasket can be replaced without any tools
- Heating element conceal in door frame to eliminate any condensation
- Designed to accommodate 1 number of GN 1/1 in pan size
- Temperature : 29 to 46°F / -2 to 8°C
- Electrical: 115/60/1 with NEMA 5-15P plug, 10ft cord



NEMA 5-15P



CSSU-54GC



CSSU-71GC



CSSU-88GC

◆ Technical Data

| MODEL | DOOR | Ext. Dimensions W X D X H (In) | Int.. Dimensions W X D X H (In) | V/Hz/Ph | AMPS | STORGE CAPACITY Sq-ft | SHELF (pcs) | SHIP WEIGHT LBS | NEMA PLUG |
|-----------|------|-----------------------------------|------------------------------------|----------|------|-----------------------------|----------------|-----------------------|--------------|
| CSSU-54GC | 2 | 48.03x27.6x33.9 | 31.3x22.8x22 | 115/60/1 | | 10.6 | 2 | 216 | 5-15P |
| CSSU-71GC | 3 | 66.15x27.6x33.9 | 48.43x22.8x22 | 115/60/1 | | 15.2 | 3 | 295 | 5-15P |
| CSSU-88GC | 4 | 82.28x27.6x33.9 | 65.55x22.8x22 | 115/60/1 | | 21.8 | 4 | | 5-15P |



If the data and structure update, without notice, subject to material object.